



PLAN

NOTES

1. All dimensions are in millimetres unless noted otherwise.
2. Where path infrastructure is located further from the lot boundary splays may be reduced to a minimum of 1.5m x 1.5m
3. Light levels at the crossover must comply with AS1158.3.1-2020 Lighting for roads and public spaces Pedestrian area (Category P) lighting - Performance and design requirements, Lighting category to be assessed on a case by case basis and approved by Council.
4. Lighting is to be carefully targeted to avoid excessive illumination, up lighting and spill light and align with Australian Standard AS 4282-1997: Control of obtrusive effects of outdoor lighting.

APPROVED FOR USE		FEB 2023
No	Revision	Date

Disclaimer:
 The authors and sponsoring organisations shall have no liability or responsibility to the user or any other person or entity with respect to any liability, loss or damage caused or alleged to be caused, directly or indirectly, by the adoption and use of these Standard Drawings including, but not limited to, any interruption of service, loss of business or anticipatory profits, or consequential damages resulting from the use of these Standard Drawings. Persons must not rely on these Standard Drawings as the equivalent of or a substitute for, project-specific design and assessment by an appropriately qualified professional.



DRAWING NOT TO SCALE		Drawing Title	PROPERTY SPLAY TO LANEWAYS & VEHICLE CROSSINGS
Approved	Project Services		
Date	FEB. 2023	Original Size	A3
Drawing No:			CPP1510
Rev:			A